

BRTR09WDS5P0 Technical Specifications																		
Power source (KVA)	Power Supply (V)	Recommended IMM (T)	Traverser Stroke	Traverser Stroke (mm)	Crosswise Stroke (mm)	Vertical Stroke (mm)	Stand-by station (mm)	Max loading (Kg)	Cycle time (s)	Dry take out time(s)	Arm model	Model of EOAT	Angel	Working air pressure (MPa)	Air consumption (N-l /cycle)	Positioning accuracy (mm)	Complete machine size (mm)	Net weight (Kg)
3.5	220	160-320	AC servo motor	1500	P: 550 R: 550	950	P: 153 R: 196	8	7.03	1.5	Two arms and telescopic type	4 suction 2 fixtures	90°	0.5-0.6	4	±0.05	2280*1695*1480	300
transverse				Crosswise					Obverse arm					Deputy arm				
Transverse electrical machines	Reducer	Slide rail	Gear rack / Belt	Electrical machines	Reducer	Slide rail	Gear rack / Belt	air cylinder	Electrical machines	Reducer	Slide rail	Gear rack / Belt	Air cylinder	electrical machines	Reducer	Slide rail	Gear rack /Belt	Air cylinder
750W	750W 1: 9	25mm	belt-: 25mm	400W*2	400W*2 1: 9	20mm	gear rack: 20mm	\	750W	750W 1:9	20mm 20mm	Belt: 15mm gear rack: 25mm	\	750W	750W 1:5	20mm 20mm	belt: 15mm 25mm	\

